



Model: WS NC FOR BASALTE FIBONACCI

Model No.: 003-1-012

Family: WALL-SMART

DWG NO. 003-4-012-SPC

PRODUCT SPEC.

REVISION A

DATE 19/MAY/2021



Make Your Wall Smart

“WS NC FOR BASALTE FIBONACCI” - Product description:

The “WS NC FOR BASALTE FIBONACCI” is an adapter for in-wall flush installation of a BASALTE FIBONACCI keypad.

The “WS NC FOR BASALTE FIBONACCI” firmly mounts the keypad allowing easy access, insertion and operation.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and removal of the keypad.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in 1/2” drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use “WS Concrete Box 200x160” P/N 10-01-181 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with FIBONACCI (by BASALTE) (not included).
- Adapter kit contains:
 1. Wall adapter (x1)

Key properties:

- Dimensions (W/H/D): 199mm (7.83")/ 159mm (6.26")/ 16.6mm (0.65")
- Power Supply: None (manual adapter).
- Weight: 0.5Kg, 1.10lbs.
- Material: Moisture resistant MDF.
- To be installed in 1/2” drywall (for installation in 5/8” drywall use 1/8” shim pack P/N 10-01-067 (sold separately)).

