



Model: WS NC FOR SAVANT ASCEND WFB-3G

Family: WALL-SMART

DWG NO. 028-4-908-SPC



Model No.: 028-1-908

PRODUCT SPEC.

REVISION A  
DATE 06/SEP/2022

**Make Your Wall Smart**


**WS NC FOR SAVANT ASCEND WFB-3G - Product description:**

The "WS NC FOR SAVANT ASCEND WFB-3G" is an adapter for in-wall flush installation of a Savant Ascend 3Gang keypad.

The "WS NC FOR SAVANT ASCEND WFB-3G" firmly mounts the keypad while allowing easy access, insertion and removal.

**Key features and benefits:**

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Includes depth calibration mechanism.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/brick wall use "WS Concrete Box 250x202" P/N 100-1-813 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with SAVANT ASCEND WFB-3G. (keypad not included)
- Adapter kit contains:
  1. (X1) Wall adapter
  2. (X6) M3 nuts
  3. (X1) Keypad adapter
  4. (X6) M3x12 screws



**Key properties:**

- Dimensions (W/H/D): 248.9mm (9.8")/ 200.7mm (7.9")/ 44mm (1.73").
- Power Supply: None (manual adapter).
- Weight: 0.6Kg, 1.32lbs.
- Material: Moisture resistant MDF (compliant with TSCA Title VI).
- To be installed in 1/2" drywall (for installation in 5/8" drywall use 1/8" shim pack P/N 10-01-067 (sold separately)).

