



Model: WS NC FOR IC REALTIME
IPMX-W40F-IRW2

Model No.: 076-1-875

Family: WALL-SMART

DWG NO. 076-4-875-SPC

PRODUCT SPEC.

REVISION A

DATE 27/DEC./2020



Make Your Wall Smart

“WS NC FOR IC REALTIME IPMX-W40F-IRW2” - Product description:

The “WS NC FOR IC REALTIME IPMX-W40F-IRW2” is an adapter for in-wall\ceiling flush installation of IC REALTIME IPMX-W40F-IRW2 camera.

The “WS NC FOR IC REALTIME IPMX-W40F-IRW2” firmly mounts the device while allowing easy access, insertion and operation.

Key features and benefits:

- Flush with the wall\ceiling.
- Paintable with the wall\ceiling paint in any color and texture.
- Allows easy insertion and removal of the camera.
- The adapter is supplied unpainted (To be painted after installation as part of the wall\ceiling).
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- Designed for the use with IC REALTIME IPMX-W40F-IRW2 (not included).
- Adapter kit contains:
 1. (x1) Wall adapter
 2. (x1) Camera adapter
 3. (x1) Face plate
 4. (x4) M4x12 Cap screws
 5. (x4) M4 nuts

Key properties:

- Dimensions (W/H/D): 201mm (7.91")/ 201mm (7.91")/ 65.0mm (2.56")
- Power Supply: None (manual adapter).
- Weight: 0.6Kg, 1.32lbs.
- Material: Moisture resistant MDF
- To be installed in 1/2" drywall (for installation in 5/8" drywall use 1/8" shim pack P/N 10-01-067 (sold separately)).

INSTALLATION POSITION:
POINT WALL-MOUNT TO
GENERAL VIEW DIRECTION
OF THE CAMERA AS
MARKED BY THE ARROW

